

DS-K1107M/MK

Card Reader

- LED Indicator Displays Reader Status
- Tamper-Resistant Alarm
- Supports Mifare Cards
- Keypad (Optional)
- RS-485 and Wiegand (W26/W34) Protocols

Hikvision DS-K1107M/MK card readers support RS-485 and Wiegand (W26/W34) protocols.

The built-in 13.56 MHz Mifare card reading module meets the ISO 14443-A standard and reads Mifare ID cards.

Available Models: DS-K1107M/MK: Mifare card reader w/keypad



	DS-K1107M	DS-K1107MK
Processor	32-bit	
Reading Range	<input type="checkbox"/> 1.97" (<input type="checkbox"/> 50 mm)	
Card Type	Mifare cards	
ID Settings	via DIP switch	
Communication Protocols	RS-485/Wiegand (set via DIP switch)	
Audio Alert	Beeper	
Keypad	No keypad	Keypad w/12 keys (0 to 9, *, #)
LED Indicator	Power indicator, status indicator	
Working Temperature	-4° to 149° F (-20° to +65° C)	
Working Humidity	10% to 90% (non-condensing)	
Dimensions	4.53" x 1.73" x 0.87" (115 mm x 44 mm x 22 mm)	
Tamper Alarm	Supported	
Protection Level	IP65	
Certifications	CE, FCC, UL 60950-1	
Power Supply	12 VDC	
Power Consumption	<input type="checkbox"/> 2 W	
Installing Method	Wall mounting with screws, does not support gang box	