

DS-D5027UC

27" 4K Monitor

- High-Definition Image Quality, High Brightness, 4K Ultra-Clear Display, Outstanding Image
- Super Wide Viewing Angle Screen (up, down, left and right) 178°
- Adaptive Reappearance Rate of Signal Input Status Image
- High-Definition Digital Audio Coaxial Output with Strong Anti-Interference Ability
- The HDMI/DP Interface Supports Ultra High-Definition Image Input, and the PC Interface Is Compatible with Analog Device Access




Available Model

DS-D5027UC

Specifications

DS-D5027UC	
Backlight	LED backlight
Screen Size	27 inch
Resolution	3840 × 2160 @ 60 Hz
Brightness	350 cd/m ²
Contrast	1000:1
Response Time	14 ms
Color	8 bit + FRC (1.07G)
Active Area	596.736 mm (H) × 335.664 mm (V)
Viewing Angle	Horizontal 178°, vertical 178°
Interfaces	1 x HDMI input
	1 x DP input
	1 x AUDIO output
Power Supply	100 to 240 VAC, 50/60 Hz
Power Consumption	≤56 W
Standby Power Consumption	≤0.5 W
Working Temperature	32° to 104° F (0° to 40° C)
Working Humidity	10% to 80% (non-condensing)
Storage Temperature	-4° to 140° F (-20° to 60° C)
Storage Humidity	10% to 80% (non-condensing)
Material of Casing	Plastic
Color of Casing	Black
VESA	100 mm x 100 mm, 4-M4 x 10 mm
Loudspeaker	2 * 2 W
Dimensions (w x h x d)	24.18" x 15.76" x 9.827" (614.19 mm x 400.4 mm x 249.6 mm)
Packing Dimensions (w x h x d)	27.2" x 5.5" x 18.9" (690 mm x 140 mm x 480 mm)
Gross Weight	14 lb 7 oz (6.55 kg)
Net Weight	11 lb 3 oz (5.07 kg)
Included Accessories	User manual
	Power cord
	Pedestal
	12 ft (1.5 m) HDMI cable

Interfaces



No.	Label	Description
1	HDMI	HDMI 2.0, 3840*2160 @ 60 Hz
2	DisplayPort IN	DP input, 3840*2160 @ 60 Hz
3	AUDIO OUT	3.5 mm audio output

Dimensions

