

## DS-K1T502DBWX-C Video Access Control Terminal



- Manage access control, video intercoms, and video security with one device
- IP65 & IK09 protections, as well as increased stability with zinc alloy materials
- Multiple authentication methods, including card, etc.
- Remote control via the Hik-Connect mobile app
- Connects to external access controller via Wiegand protocol
- Two-way audio via SIP 2.0 protocol
- RS-485 communication for connecting external card reader


## ▪ Specification

System	
Operating system	Linux
Video	
Lens	1
Resolution	2 MP
FOV	HFOV = 110°; VFOV = 81°
Video standard	PAL (Default) and NTSC
Network	
Wired network	10 M/100 M self-adaptive
Wi-Fi	Support
Bluetooth	Support
Interface	
Network interface	1
Lock control	1
Exit button	1
Door contact input	1
Alarm input	1
Alarm output	1
TAMPER	1
RS-485	1
Wiegand	1 (Output only)
SD card	1
Capacity	
Card capacity	100,000
Event capacity	300,000
Authentication	
Card type	Mifare 1 card, DESfire card
Card reading distance	0 ~ 3 cm
Function	
Two-way audio	Support
Hik-Connect	Support
General	
Power supply	1 A (DC 12 V ~ DC 24 V)
Power consumption	≤12 W
Working temperature	-40 °C ~ +70 °C (-40 °F ~ +158 °F)
Protective level	IK09, IP65

## ▪ Available Model

DS-K1T502DBWX-C

▪ Dimension



**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

