

DS-MDS003/2T/8(0-STD) Body Camera Docking Station



- Stable Dual System Design
- Wall, Mobile, and Desktop Mount
- 13.3" Touchscreen, 1920 × 1080 Resolution
- Unlock by Touchless Identity Authentication
- Connect Up to Four 8-Camera Stations
- Auto Charging
- Two USB Ports: 1 for Mouse/Keyboard/Flash Disk Upgrade, 1 Reserved
- Standard 2 TB Drive, Six 8 TB Drive Bays
- RAID 0, RAID 1, and RAID 5
- Auto Upload Picture, Video, Audio; Clear Storage
- Lock Important Data
- Data Protected from Sudden Power Cutoff
- Log Management
- Overwrites Data According to Collection Sequence when Storage Full
- ANR Uploading Prevents Data Loss
- File Search Video, Audio, and Playback
- Multi-Users
- Upload to CVR and Cloud Storage

The DS-MDS003/2T/8(0-STD) Body Camera Docking Station provides an easy way to access body cameras, and collect, store, and play audio, video, and picture files in the connected body cameras.

Available Model

DS-MDS003/2T/8(0-STD)







FC

Specifications

-			
Screen			
Screen Size	13.3"		
Resolution	1920 × 1080		
Touchscreen	Capacitive touchscreen		
Smart Function			
Face Picture Comparison	Body camera access by Touchless Identity Authentication		
General			
Operating System	Linux, Android 5.1.1		
Memory	2 GB		
Indicator	Charging indicator, working indicator		
Button	Power button		
Product Weight	18.295 kg (40.334 lb)		
Product Dimensions	635 mm × 604.6 mm × 108.7 mm (25" × 23.8" × 4.3")		
Package Weight	24.1 kg (53.13 lb)		
Package Dimension	793 mm × 393 mm × 578 mm (31.2" × 15.5" × 22.8")		
Ingress Protection	IP20		
Power Supply Mode	External power supply		
Working Temperature	-10° to 55° C (14° to 131° F)		
Working Humidity	RH (93 ±3)%		
Storage Temperature	-25° to 50° C (-13° to 122° F)		
Light Supplement			
White Light	Supported		
Storage			
Standard	2 TB		
Number of Extended Storage Bays	6		
Extended Storage Media	Hard disk		
Extended Storage Capacity	Maximum 8 TB each		
Peripheral Device Interface			
Charging Interface	Three-phase plug		
External Interface	RJ-45, RS-232, USB 2.0, USB 3.0		
Loudspeaker	Supported		


<u>Dimensions</u>





E





Unit: mm



Accessories

NOT INCLUDED				
H				
DS-MH1601	DS-MH1602	DS-MH1901	DS-MH1902	
Desktop Bracket Assembly	Moving Bracket Assembly	Wall Mounted Bracket,	Wall Mounted Bracket,	
		Main Bracket (1-2)	Main Bracket (3-4)	

