

DS-2CD2525FWD-IS

2 MP Outdoor EXIR Fixed Mini Network Dome Camera



- **1/2.8" (2 MP) Progressive Scan CMOS**
- **Full 1080p Resolution @ 60 fps**
- **Minimum Illumination:** Color: 0.009 lux @ (f/1.6, AGC on), 0 lux with IR
- **Powered by Darkfighter**
- **Up to 30 ft (10 m) EXIR 2.0 Range**
- **2.8 mm, 4 mm, or 6 mm Lens**
- **H.265+, H.265, H.264+, H.264**
- **120 dB True WDR**
- **MicroSD Card Slot Supports 128 GB**
- **IP66, IK08 Protection**
- **12 VDC and PoE (802.3af)**

The Hikvision DS-2CD2525FWD-IS Outdoor EXIR Fixed Mini Network Dome Camera provides high definition output. It supports H.265+ video compression, which assures savings in bandwidth and storage.

The camera is equipped with a 2.8 mm, 4 mm, or 6 mm lens and offers an EXIR 2.0 range of up to 30 ft (10 m).

Smart features such as line crossing, intrusion, unattended luggage, and scene change detection are also supported.








Available models:
DS-2CD2525FWD-IS




Specifications

DS-2CD2525FWD-IS	
Camera	
Image Sensor	1/2.8" progressive scan CMOS
Minimum Illumination	Color: 0.009 lux @ (f/1.6, AGC on), 0 lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Day/Night	IR cut filter
Digital Noise Reduction	3D DNR
WDR	120 dB
Three-Axis Adjustment	Pan: -30° to +30°, tilt: 0° to 75°, rotate: 0° to 360°
Lens	
Focal Length	2.8 mm, 4 mm, or 6 mm
Aperture	f/1.6
FOV	2.8 mm: Horizontal FOV: 108°, vertical FOV: 59°, diagonal FOV: 129° 4 mm: Horizontal FOV: 87°, vertical FOV: 45°, diagonal FOV: 102° 6 mm: Horizontal FOV: 53°, vertical FOV: 29°, diagonal FOV: 60°
Lens Mount	M12
IR	
IR Range	Up to 30 ft (10 m)
Wavelength	850 nm
Compression Standard	
Video Compression	Main stream: H.265+/H.265/H.264+/H.264; sub stream: H.265+/H.265/H.264+/H.264/MJPEG; third stream: H.265+/H.265/H.264+/H.264
H.264 Type	Main profile/high profile
H.264+	Yes
H.265 Type	Main profile
H.265+	Yes
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G722.1/G711 ulaw/G711 alaw/G726/MP2L2/PCM
Audio Bit Rate	64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)
Smart Features	
Behavior Analysis	Line crossing detection, intrusion detection, unattended baggage detection, object removal detection
Face Detection	Yes
Region of Interest	Supports one fixed region for main stream and sub-stream
Image	
Maximum Resolution	1920 × 1080
Main Stream	60 fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub Stream	30 fps (640 × 480, 640 × 360, 320 × 240)
Third Stream	30 fps (1280 × 720, 640 × 360, 352 × 240)
Image Enhancement	BLC/3D DNR
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or Web browser
Day/Night Switch	Auto/schedule/day/night/triggered by alarm in
Network	
Network Storage	Supports microSD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering, network disconnected, IP address conflict, HDD full, HDD error, illegal login
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1x, QoS, IPv6
General Function	One-key reset, anti-flicker, three streams, heartbeat, password protection, privacy mask, watermark, IP address filter
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users; 3 levels: administrator, operator, and user
Client	iVMS-4200, iVMS-4500, Hik-Connect
Web Browser	IE 8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
Interface	
Audio	Two inputs: line in (3.5 mm) or microphone in (built-in microphone), 1 output: line out (3.5 mm), mono sound
Alarm	One input: alarm in (3.5mm), one output: alarm out (3.5 mm)
Communication Interface	1-port RJ-45 10M/100M self-adaptive Ethernet port
On-Board Storage	Built-in microSD/SDHC/SDXC slot, up to 128 GB
SVC	H.264 and H.265 encoding
Audio	
Environment Noise Filtering	Yes
Audio Sampling Rate	16 kHz, 32 kHz, 44.1 kHz, 48 kHz
General	
Operating Conditions	-22° to 140° F (-30° to 60° C), humidity 95% or less (non-condensing)
Power Supply	12 VDC ±25%, PoE (802.3af, class 3)
Power Consumption and Current	12 VDC, 0.7 A, maximum 7.5 W, PoE (802.3af, 36 V to 57 V), 0.3 A to 0.1 A, maximum 9.5 W
Protection Level	IP66, IK08, TVS 2000V lightning protection, surge protection and voltage transient protection
Material	Metal and plastic
Dimensions	Ø4.33" × 2.22" (Ø110 mm × 56.4 mm)
Weight	0.88 lbs (0.40 kg)

Accessories (Not Included)

						
WMS Wall Mount w/Junction Box	PC120 Pendant Cap	CPM Ceiling Pendant Mount	CM Corner Mount	PM Pole Mount	GP120 Gang Plate	CBD-MINI Conduit Base

Dimensions



Box Contents (Subject to Change without Notice)

Quick Start Guide
Bracket Ring
Screws
Watertight Cable Connector