

DS-2CE16U1T-ITF 8 MP Outdoor Bullet Camera

TurboHD™



- 8 MP High Performance CMOS
- Up to 3840 x 2160 Resolution
- 2.8 mm and 6 mm Fixed Lens Options
- 3D DNR, DWDR
- EXIR 2.0 up to 100 ft (30 m) IR Range
- Multiprotocol Output:
TVI/AHD/CVI/CVBS
- Up-the-Coax (HIKVISION-C)
- IP67 Protection

The Hikvision DS-2CE16U1T-ITF 8 MP Outdoor Bullet Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 100 feet (30 meters).

The 2.8 mm and 6 mm fixed lens options are optimized for viewing angles that fit any situation. DWDR (Digital Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

Available models:
DS-2CE16U1T-ITF



Specifications

DS-2CE16U1T-ITF

Camera

Image Sensor	8.29 MP progressive scan CMOS
Frame Rate	TVI: 8 MP @ 12.5 fps, 8 MP @ 15 fps, 5 MP @ 20 fps, 4 MP @ 25 fps, 4 MP @ 30 fps, 2 MP @ 25 fps, 2 MP @ 30 fps CVI: 8 MP @ 12.5 fps, 8 MP @ 15 fps AHD: 8 MP @ 12.5 fps, 8 MP @ 15 fps CVBS: 960H NTSC
Resolution	3840 (H) × 2160 (V)
Minimum Illumination	Color: 0.01 Lux @ (f/1.2, AGC on), 0 Lux with IR
Shutter Speed	1/15 s to 1/50,000 s
Lens	2.8 mm and 6 mm fixed lens options
Horizontal Field of View	102.2° (2.8 mm), 50.8° (6 mm)
Lens Mount	M16
Day/Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°; tilt: 0° to 180°; rotate: 0° to 360°
Synchronization	Internal synchronization
DWDR	105 dB

Menu

AGC	Yes
Day/Night Mode	Auto/color/BW (black and white)
White Balance	Auto/manual
BLC	Yes
Language	English
Functions	Brightness, sharpness, DNR, mirror, Smart IR, HLC

Interface

TVI Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS

General

Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25% (only one power supply can be used per camera)
Power Consumption	Maximum 5.3 W
Protection Level	IP67
Material	Front cover: metal, main body: plastic, bracket: metal
IR Range	Up to 100 ft (30 m)
Communication	Up-the-Coax, protocol: HIKVISION-C (TVI output)
Dimensions	2.28" x 2.40" x 6.42" (58 mm × 61 mm × 159.8 mm)
Weight	Approximately 0.76 lbs (345 g)

Accessories



Dimensions

