

DS-2CE57D3T-VPITF(B)

2 MP Outdoor Ultra-Low Light Dome Camera



- 2 MP High Performance CMOS
- Up to 1080p Resolution
- Ultra-Low Light
- 2.8 mm, 3.6 mm, and 6 mm fixed lens options
- EXIR 2.0 up to 100 ft (30 m) IR Range
- Smart IR
- 120dB True WDR, 3D DNR
- Multiprotocol Output: TVI/AHD/CVI/ CVBS
- Up-the-Coax (HIKVISION-C)
- Black-Finish Housing Available
- IP67, IK10 Protection

The Hikvision DS-2CE57D3T-VPITF(B) 2 MP Outdoor Ultra-Low Light Dome Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 100 feet (30 meters).

The 2.8 mm, 3.6 mm, and 6 mm fixed lens options are optimized for viewing angles that fit any situation. True 120db WDR (Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

Available models:

DS-2CE57D3T-VPITF
DS-2CE57D3T-VPITFB



Specifications

DS-2CE57D3T-VPITF		DS-2CE57D3T-VPITFB	
Camera			
Image Sensor	2.0 megapixel progressive scan CMOS		
Signal System	NTSC		
Video Frame Rate	1080p @ 30 fps		
Resolution	1920 (H) × 1080 (V)		
Minimum Illumination	Color: 0.005 lux @ (f/1.2, AGC on), 0 lux with IR		
Shutter Speed	1/30 s to 1/50,000s		
Lens	2.8 mm, 3.6 mm, and 6 mm fixed lens options		
Horizontal Field of View	106° (2.8 mm), 82° (3.6 mm), 51° (6 mm)		
Lens Mount	M12		
Day/Night	IR cut filter		
Angle Adjustment	Pan: 0° to 340°, tilt: 0° to 75°, rotate: 0° to 360°		
Synchronization	Internal synchronization		
WDR (Wide Dynamic Range)	>120 dB		
Menu			
AGC	High/medium/low		
D/N Mode	Auto/color/BW (black and white)		
Image Mode	Standard/high-sat		
BLC (Backlight Compensation)	Yes		
WDR	Yes		
3D DNR	Level 1 to 9		
Language	English		
Functions	Brightness, sharpness, 3D DNR, mirror, smart IR		
Interface			
Video Output	1 HD analog output		
Switch Button	TVI/AHD/CVI/CVBS		
General			
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)		
Power Supply	12 VDC ± 20%		
Power Consumption	Maximum 4.6 W		
Ingress Protection	IP67, IK10		
Material	Metal		
Color	Hikvision White	Hikvision Black	
IR Range	Up to 100 ft (30 m)		
Dimensions	Ø4.4" × 3.2" (Ø111 mm × 82.4 mm)		
Weight	Approximately 1.07 lbs (487 g)		

Accessories (not included)

									
WMS + PC110 Wall Mount Short + 110 mm Pendant Cap	CB110 Conduit Base	AB110 Angled Base	CPM + PC110 Ceiling Pendant Mount + 110 mm Pendant Cap	WM110 Plastic Wall Mount	PM Pole Mount	WMSB Wall Mount Short (Black)	CB110B Conduit Base (Black)	AB110B Angled Base (Black)	WM110B Plastic Wall Mount (Black)

Dimensions

