

DS-2CE71D0T-PIRL

2 MP Outdoor PIR Turret Camera

TurboHD™



- 2 MP High Performance CMOS
- Up to 1920 x 1080 Resolution
- 2.8 mm and 3.6 mm Fixed Lens Options
- EXIR 2.0 up to 65 ft (20 m) IR Range
- PIR Detection and Visual Alarm
- White Light Emitter
- Up-the-Coax (HIKVISION-C)
- IP67 Protection

The Hikvision DS-2CE71D0T-PIRL 2 MP Outdoor PIR Turret Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

The PIR camera line is equipped with a PIR sensor and White Light (WL) emitter that is used to provide intelligent human detection and alarming to deter intruders, integrated with the host DVR.

EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 65 feet (20 meters).

The 2.8 mm and 3.6 mm fixed lens options are optimized for viewing angles that fit any situation.

Available models:

DS-2CE71D0T-PIRL:

2.8 mm to 3.6 mm lenses








Specifications

DS-2CE71D0T-PIRL

Camera	
Image Sensor	2 MP progressive scan CMOS
Signal System	NTSC
Frame Rate	1080p @ 30 fps
Resolution	1920 (H) × 1080 (V)
Minimum Illumination	Color: 0.01 lux @ (f/1.2, AGC on), 0 lux with IR
Shutter Time	1/30 s to 1/50,000 s
Lens	2.8 mm, 3.6 mm fixed focal lens
Horizontal Field of View	103° (2.8 mm), 82.2° (3.6 mm)
Lens Mount	M12
Visual Alarm	Yes
Day/Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotate: 0° to 360°
Synchronization	Internal synchronization
Menu	
White Light	Alarm/off
AGC	Low/middle/high
Day/Night	Auto/color/BW (Black and White)
White Balance	Auto/manual
Backlight Compensation	Yes
Language	English
Functions	Brightness, contrast, sharpness, saturation, DNR, mirror
Interface	
Video Output	1 HD analog output
General	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25%
Power Consumption	Maximum 4 W
Protection Level	IP67
Material	Front cover: metal, main body: plastic
IR Range	Up to 65 ft (20 m)
PIR Range	Angle: 110°, Range: 35 ft (11 m)
Communication	Up-the-Coax, Protocol: HIKVISION-C (HD-TVI output)
Dimensions	Ø 4.32" × 3.53" (Ø 109.8 mm × 89.75 mm)
Weight	Approximately 0.68 lbs (310 g)

Accessories

				
WMS + PC110T Wall Mount and Junction Box with 110 mm Pendant Cap	PM Pole Mount	CM Corner Mount	CBS Junction Box	ABS Angled Base

Dimensions

