

DS-2CE76D3T-ITMF(B)

2 MP Outdoor Ultra-Low Light Turret Camera



- 2 MP High Performance CMOS
- Up to 1080p Resolution
- Ultra-Low Light
- 2.8 mm, 3.6 mm, 6 mm Fixed Lens Options
- EXIR 2.0 up to 100 ft (30 m) IR Range
- Smart IR
- 120 dB True WDR, 3D DNR
- Multiprotocol Output: TVI/AHD/CVI/CVBS
- Up-the-Coax (HIKVISION-C)
- Black-Finish Housing Available
- IP67 Protection

The Hikvision DS-2CE76D3T-ITMF(B) 2 MP Outdoor Ultra-Low Light Turret Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 100 feet (30 meters).

The 2.8 mm, 3.6 mm, and 6 mm lens options are optimized for viewing angles that fit any situation. True 120 db WDR (Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.







Available models:
DS-2CE76D3T-ITMF
DS-2CE76D3T-ITMFB



Specifications

	DS-2CE76D3T-ITMF	DS-2CE76D3T-ITMFB
Camera		
Image Sensor	2.0 megapixel progressive scan CMOS	
Signal System	NTSC	
Video Frame Rate	1080p @ 30 fps	
Resolution	1920 (H) × 1080 (V)	
Minimum Illumination	Color: 0.005 lux @ (f/1.2, AGC on), 0 lux with IR	
Shutter Speed	1/30 s to 1/50,000s	
Lens	2.8 mm, 3.6 mm, and 6 mm fixed lens options	
Horizontal Field of View	106° (2.8 mm), 82° (3.6 mm), 51° (6 mm)	
Lens Mount	M12	
Day/Night	IR cut filter	
Angle Adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°	
Synchronization	Internal synchronization	
WDR (Wide Dynamic Range)	>120 dB	
Menu		
AGC	High/medium/low	
D/N Mode	Auto/color/BW (black and white)	
Image Mode	Standard/high-sat	
BLC (Backlight Compensation)	Yes	
WDR	Yes	
3D DNR	Level 1 to 9	
Language	English	
Functions	Brightness, sharpness, 3D DNR, mirror, smart IR	
Interface		
Video Output	1 HD analog output	
Switch Button	TVI/AHD/CVI/CVBS	
General		
Operating Conditions	-40° to 140° F [-40° to 60° C], humidity: 90% or less (non-condensing)	
Power Supply	12 VDC ±25%	
Power Consumption	Maximum 4.6 W	
Ingress Protection	IP67	
Material	Metal	
Color	Hikvision White	Hikvision Black
IR Range	Up to 100 ft (30 m)	
Dimensions	3.52" × 2.68" [89.47 mm × 68.2 mm]	
Weight	Approximately 0.53 lbs (240 g)	

Accessories (not included)

					
WML + PC110T Wall Mount Long + 110 mm Pendant Cap	PM Pole Mount	CM Corner Mount	CBXS Conduit Base	WMSB Wall Mount Short (Black)	CBXSB Conduit Base (Black)

Dimensions

