

PRODUCT QUICK GUIDE

FALL/WINTER 2021



ColorVu



HIKVISION PRODUCT FAMILIES AND TOP SELLERS

VALUE SERIES FAMILY

- H.265+ compression
- 2, 4, 8 MP (4K) resolution
- Multiple lens options
- True WDR, EXIR 2.0 IR
- Audio/Alarm Input/Output Option
- IP67, PoE/12VDC
- -30 to 60 °C (-22 to 140 °F)



**DS-2CD2523G0-IS
DS-2CD2543G0-IS /
ISB(black)**

- 2 MP/4MP, 2.8/4 mm lens options
- 120 dB True WDR, 10m IR
- 3-Axis Gimbal
- Brackets: WMS(B), PC120(B), GP120, CB120



**DS-2CD2143G0-I
DS-2CD2143G0-IB
(black)
DS-2CD2183G0-I
DS-2CD2183G0-IB
(black)**

- 4 MP/8MP, 2.8/4 mm lens options
- 120 dB True WDR, 30m IR
- Vandal Resistant, 3-Axis Gimbal
- Brackets: WML, PC110, PM, CM, CB110



**DS-2CD2343G0-I
DS-2CD2343G0-IB
(Black)
DS-2CD2383G0-I
DS-2CD2383G0-IB
(black)**

- 4 MP/8MP, 2.8/4 mm lens options
- 120 dB True WDR, 30m IR
- Vandal Resistant, 3-Axis Gimbal
- Brackets: WML, PC130T, PM, CM, CB130T



**DS-2CD2743G1-IZS
DS-2CD2743G1-IZSB
(black)
DS-2CD2783G1-IZS
DS-2CD2783G1-IZSB
(black)**

- 4 MP/8MP, 2.8 - 12 mm motorized zoom
- 120 dB True WDR, 30m IR
- Vandal Resistant, 3-Axis Gimbal
- Brackets: WML+PC155, CB155, CPM+PC155, PM, CM

5 MP TURBOHD H0T CAMERA FAMILY

- Full line of fixed and varifocal models
- EXIR 2.0, BLC, True Day/Night, UTC menu
- IP67 ingress protection



DS-2CE57H0T-VPITF

- Turbo Dome 5MP
- 20 meters IR
- 2.8/3,6 mm Lens
- Brackets: PC110, WML, PM, CM, CB110



DS-2CE76H0T-ITMF

- Turbo Turret 5MP
- 20 meters IR
- 2.8/3,6mm Lens
- Brackets: PC110T, PM, CBXS, WML

ACUSENSE NVR

- Intelligent analytics based on deep learning algorithm
- Up to 4-ch perimeter protection
- Up to 8-ch IP camera inputs



DS-7608NXI-I2/8P/5

- 8-ch 4K UHD NVR
- 80 Mbps Incoming Bandwidth
- Facial detection and Human/Vehicle analytics

PERFORMANCE SERIES FAMILY



- 5, 8MP(4K) resolution
- 120dB True WDR, EXIR 2.0 IR
- Powered by DarkFighter
- Filter alarms for only human or vehicle
- Wide array of video analytics
- SL model includes strobe light and alarm
- IP66, PoE/12VDC
- -30 to 60°C (-22 to 140 °F)



PCI-D15F2S

- 5MP, 2.8/4 mm lens options
- 120 dB True WDR, 40m IR
- Vandal Resistant, 3-Axis Gimbal
- Powered by DarkFighter
- Filter alarms for only human or vehicle
- Brackets: PC120, CB120, WMS, CPM



PCI-T18F2S

- 8MP, 2.8/4 mm lens options
- 120 dB True WDR, 40m IR
- Vandal Resistant, 3-Axis Gimbal
- Powered by DarkFighter
- Filter alarms for only human or vehicle
- Brackets: PC140, CB140PT, CPM, WML



PCI-T15F2SL

- 5MP, 2.8/4 mm lens options
- 120 dB True WDR, 40m IR
- Vandal Resistant, 3-Axis Gimbal
- Powered by DarkFighter
- Filter alarms for only human or vehicle
- build-in mic, Strobe Light and Audio Alarm
- Brackets: PC140, CB140PT, CPM, WML



PCI-LB15F2SL

- 5MP, 2.8/4/6/12 mm lens options
- 120 dB True WDR, 60m IR
- Vandal Resistant, 3-Axis Gimbal
- Powered by DarkFighter
- Filter alarms for only human or vehicle
- build-in mic, Strobe Light and Audio Alarm
- Brackets: CB130, PM, CM

LED MONITORS

- LED-Backlit TFT LCD screen
- 5 ms response time
- Video inputs 1x HDMI, 1x VGA
- Plastic bezel



DS-D5024FC

- 23.6" Screen size with BNC & USB
- 1920 x 1080 Resolution



DS-D5024FN

- 23.8" Screen size
- 1920 x 1080 Resolution

ColorVu FAMILY

- Color images in darkness
- Wide f/1.0 lens aperture
- True WDR, supplemental light



- Wide array of video analytics
- IP67, PoE/12VDC



DS-2CD2T47G1-L

- 4MP, 2.8/4/6mm lens options
- 120 dB True WDR
- Vandal Resistant, 3-Axis Gimbal
- 24/7 Color with White Light
- Brackets: CBS, CB130, CM, PM



DS-2CD2347G1-L

- 4MP, 2.8/4 mm lens options
- 120 dB True WDR
- Vandal Resistant, 3-Axis Gimbal
- 24/7 Color with White Light
- Brackets: CPM, PC140, CB140PT, WML, CM, PM



DS-2CD2087G2-L

- 8MP, 2.8/4mm lens options
- 130 dB True WDR
- Vandal Resistant, 3-Axis Gimbal
- 24/7 Color with White Light
- Brackets: CBS



DS-2CD2147G2-SU

- 4MP, 2.8/4mm lens options
- 130 dB True WDR
- Vandal Resistant, 3-Axis Gimbal
- 24/7 Color Image
- Filter alarms for only human or vehicle
- Brackets: PC120, CB120, WML

DIGITAL VIDEO RECORDERS

Professional High performance



DS-7204HQHI-K1-1TB

- 4-ch 2 MP DVR with 1 TB HDD
- 72 Mbps In/Outgoing Bandwidth



DS-7208HQHI-K2-2TB

- 8-ch 2 MP DVR with 2 TB HDD
- 96 Mbps In/Outgoing Bandwidth



DS-7204HUHI-K1-1TB

- 4-ch 5 MP DVR with 1TB HDD
- 96 Mbps In/Outgoing Bandwidth



DS-7208HUHI-K2-2TB

- 8-ch 5 MP DVR with 2 TB HDD
- 128 Mbps In/Outgoing Bandwidth

NETWORK VIDEO RECORDERS

DS-7600NI-Q VALUE SERIES

- 4, 8 or 16-ch models with integrated PoE
- H265+, up to 8 MP (4K), HDMI, 1 or 2 SATA
- Field or factory installed HDD up to 6 TB
- No charge VMS (iVMS-4200)
- Free Hik-Connect service & mobile apps



DS-7604NI-Q1/4P-2TB

- 4-ch 4K UHD NVR with 2 TB HDD
- 40 Mbps Incoming Bandwidth



DS-7608NI-Q2/8P-2TB

- 8-ch 4K UHD NVR with 2 TB HDD
- 80 Mbps Incoming Bandwidth



DS-7616NI-Q2/16P-2TB

- 16-ch 4K UHD NVR with 2 TB HDD
- 160 Mbps Incoming Bandwidth



DS-7608NI-I2/8P-4TB

- 8-ch 12 MP UHD NVR with 4 TB HDD
- 80 Mbps Incoming Bandwidth



DS-7716NI-I4/16P-4TB

- 16-ch 12 MP UHD NVR with 4 TB HDD
- 160 Mbps Incoming Bandwidth



DS-7732NI-I4/24P-4TB

- 32-ch 12 MP UHD NVR with 4 TB HDD
- 320 Mbps Incoming Bandwidth

NETWORK VIDEO RECORDERS—I PERFORMANCE SERIES

- 8, 16 or 32-ch models with integrated PoE
- H265+, up to 12 MP, HDMI, 1 or 2 SATA
- Field or factory installed HDD up to 12 TB
- No charge VMS (iVMS-4200)
- Free Hik-Connect service & mobile apps

SCAN TO
DOWNLOAD APP



SCAN TO
VIEW PRODUCT
SELECTOR



HIKVISION PRODUCT FAMILIES AND TOP SELLERS

COLORVU TurboHD DF SERIES

- 24/7 color images
- Supplemental white light
- 12 VDC, IP 67



IP VIDEO INTERCOM

- Fully integrated with Hik-Connect mobile app
- IP indoor and outdoor stations support standard PoE
- Modular door station expands up to 8 modules
- Ideal for one to many tenants



DS-2CE72DFT-F

- ColorVu outdoor Turret 2MP
- 20 meters Friendly Lighting
- 2.8/3.6mm Lens
- 130dB True WDR
- 12 VDC, IP 67
- Brackets: CBS, WMS, PC110T



DS-2CE72HFT-F

- ColorVu outdoor Turret 5MP
- 20 meters Friendly Lighting
- 2.8/3.6mm Lens
- 130dB True WDR
- 12 VDC, IP 67
- Brackets: CBS, WMS, PC110T



**DS-KH8350-WTE1
DS-KH6320-WTE1**

- IP Video Intercom Indoor Station
- Premium thin 7" touchscreen
- Record on micro SD card (sold separately)
- Live view surveillance cameras
- LAN (PoE 802.3af), Wi-Fi (12V DC)




**DS-KD8003-IME1/
Surface**

- Expandable Surface Mount IP Door Station
- 2MP camera, 180° Wide FOV at Full HD 1080p
- See clearly day and night with WDR and IR
- Communicate clearly with noise/echo cancellation
- One call button and two lock control relays



**DS-KD8003-IME1/
Flush**

- Expandable Flush Mount IP Door Station
- 2MP camera, 180° Wide FOV at Full HD 1080p
- See clearly day and night with WDR and IR
- Communicate clearly with noise/echo cancellation
- One call button and two lock control relays



**DS-KD-KK, DS-KD-KP,
DS-KD-M**

- Expandable Door Station Modules
- -KK: Name tag module with six call buttons
- -KP: Keypad module dials up to 500 rooms and enter by code
- -KP: Keypad module supports access by code
- -M: Mifare card reader module
- -DIS: Display module with 3.5" LCD Screen and 4 buttons with backlight

VALUE & SMART PRO PTZ



DS-2DE5225IW-AE

- 2MP, 1/2.8"
- 4.8 to 120 mm, 25x motorized zoom,
- 150 Meters IR Range, 120 dB True WDR
- Brackets: JBPW-L, CPM-L



DS-2DE4A425IW-DE

- 4MP, 1/2.8"
- 4.8 to 120 mm, 25x motorized zoom,
- 50 Meters IR Range, 120 dB True WDR
- Brackets: PC-DE4A, RCM-DE4A, CB-DE4A



DS-2DF8242IX-AELW

- 2MP, 1/1.8"
- 6 to 252 mm, 42x motorized zoom,
- 400 Meters IR Range, 140 dB True WDR
- Support Rapid focus; IK10, IP67, 24 VAC & Hi-PoE
- Brackets: JBPW-L, CPM-L



DS-2CD6D54FWD-IZHS

- 20 MP (4x5MP) Flexible Lens
- 2.8 to 12 mm
- IR, 120 dB True WDR
- Brackets: JBPW-L, RPM



DS-2CD6924G0-IHS

- 8 MP (4x2 MP Stitched or Separate)
- 180° Stitched
- IR, 120 dB True WDR
- Brackets: (Pendant cap included) RPM, WMP-L, JBPW-L



**DS-2CD6365G0E-IVS (6MP)
DS-2CD6365G0E-S/RC(6MP)**

- 6MP Fisheye
- 180° Stitched
- IR, 120 dB True WDR
- Brackets: CB-FE AB-FE, PC-FE-S/RC: Recessed Mount

ACCESS CONTROL

- Controllers for 2 or 4 doors with advanced features
- Advanced terminals with standalone/reader modes
- Fingerprint and facial recognition biometrics
- Video intercom access control terminals
- Readers with keypads for Mifare and Proximity cards
- HikCentral - ACS and free iVMS-4200 software



DS-K2604-G

- Four-door controller
- 4 Wiegand readers or 8 RS485 readers
- Locking metal enclosure with tamper alarm
- Compatible with 7 Ah backup battery
- ETL tested to UL294 standard



DS-K1107MK

- Keypad for access by code
- Supports RS485 and Wiegand (W26/W34)
- LED power and status indicator
- Tamper alarm, IK10, IP65



DS-K182HP

- Proximity Card Reader
- Supports Wiegand (W26)
- LED status indicator
- IP67, -40° to 149° F
- UL 294 Standard

NETWORK SWITCHES

- Full range of 5 to 28 port switches
- Unmanaged and managed options
- Standard Ethernet and PoE/PoE+
- Fast/Gigabit Ethernet and SFP options



DS-3E1309P-EI

- Smart Managed PoE+ Switch
- 8 PoE Ports with 110W Budget
- 1 Gigabit Ethernet Uplink Port
- 6kV Surge Protection



DS-3E0518P-E

- Unmanaged Gigabit PoE+ Switch
- 16 Gigabit PoE Ports with 230W Budget
- 1 Gigabit Ethernet Uplink port
- 6kV Surge Protection

DEEPINVIEW



DS-2CD7A26G0/P-IZHS
DS-2CD7A26G0/P-IZHS8
LPR Camera

- 2MP, 1/1.8"
- IZHS: 2.8 to 12 mm
- IZHS8: 8 to 32mm"
- IR, 140 dB True WDR
- License Plate Recognition
- -40 to 60 °C (-40 to 140 °F)
- Bracket: PM1/CM1/PM-LPR



DS-2CD6825G0/C-IVS
People Counting Cam

- 2MP, 1/2.7"
- 2mm, Horizontal FOV: 104.5°
- IR, Digital WDR
- People Counting
- 10 to 40 °C (14 to 104 °F)
- Bandwidth



DS-2XE6825G0-IZHS / DS-2XE6885G0-IZHS
Explosion proof bullet

- 2MP, 1/2.8 / 8MP, 1/2"
- Lens: 2.8 to 12 mm
- Lens: 8 to 32 mm"
- IR, 120 dB True WDR
- ATEX: Ex II 2 G D Ex db IIC T6 Gb/Ex tb IIIC T80°C Db IP68
- UL: Class I, Zone 1, AEx db IIC T6 Zone 21, AEx tb IIIC T80°C Ex db IIC T6 Gb X Ex tb IIIC T80°C Db X
- 100 to 240 VAC, PoE (42.5 to 57 V, 802.3 at),
- Bracket: DS-1707ZJ-Y-AC (OS)



iDS-2CD75C5G0-IZHS

- 12MP, 1/1.7"
- -Lens: 2.8 to 12 mm
- -Lens: 8 to 32mm"
- IR, 140 dB True WDR
- Audio/Alarm IN/Output
- -40 °C to 60 °C (-40 °F to 140 °F)
- 12 VDC, 0.98 A, max. 12.5 W
- PoE(802.3at)
- Bracket: WML, PC155,CPM



iDS-2CD7AC5G0-IZHS

- 12MP, 1/1.7"
- -Lens: 2.8 to 12 mm
- -Lens: 8 to 32mm"
- IR, 140 dB True WDR
- Audio/Alarm IN/Output
- -40 °C to 60 °C (-40 °F to 140 °F)
- 12 VDC, 0.98 A, max. 12.5 W
- PoE(802.3at)
- Bracket: CM1, PM1

ULTRA-HIGH RESOLUTION













SCAN TO
DOWNLOAD APP



SCAN TO
VIEW PRODUCT
SELECTOR



HIKVISION PRODUCT KITS

HIKVISION PRODUCT KITS		Camera		
Type	Model Name	Resolution	Quantity	Form Factor
IP Kit	 EKI-K41T44	4 MP	4	Turret
	 EKI-K82T46	4 MP	6	Turret
	 EKI-K164T412	4 MP	12	Turret
	 EKI-K41D44	4 MP	4	Dome
	 EKI-K82D46	4 MP	6	Dome
	 EKI-K164D412	4 MP	12	Dome
	 EKI-K82B86	8 MP	6	Bullet
	 EKI-K41B44W (Wi-Fi KIT)	4 MP	4	Bullet
Turbo Kit	 EKT-K41T24	2 MP	4	Turret
	 EKT-K82T26	2 MP	6	Turret
	 T7204U1TA4	5 MP	4	Turret
	 T7208U2TA6	5 MP	6	Turret

Camera			Recorder			
BLC/WDR	IR RANGE	Bracket	Record Type	Channel	Resolution	HDD
Yes/Digital	30	PC130T,CB130T	NVR	4-CH	up to 8MP	1 TB
Yes/Digital	30	PC130T,CB130T	NVR	8-CH	up to 8MP	2TB
Yes/Digital	30	PC130T,CB130T	NVR	16-CH	up to 8MP	4 TB
Yes/120 dB	30	PC110,CB110	NVR	4-CH	up to 8MP	1 TB
Yes/120 dB	30	PC110,CB110	NVR	8-CH	up to 8MP	2 TB
Yes/120 dB	30	PC110,CB110	NVR	16-CH	up to 8MP	4 TB
Yes/Digital	30	CBXS	NVR	8-CH	up to 8MP	2 TB
Yes/Digital	30	CBXS	NVR	4-CH	up to 4MP	1 TB
Yes/Digital	20	PC110T,CBXS	DVR	4-CH	up to 4MP	1 TB
Yes/Digital	20	PC110T,CBXS	DVR	8-CH	up to 4MP	2 TB
Yes/Digital	20	PC110T,CBXS	DVR	4-CH	up to 5MP	1 TB
Yes/Digital	20	PC110T,CBXS	DVR	8-CH	up to 5MP	2 TB



Contact Information

Toll-Free: +1-855-655-9888

Technical Support: techsupport.ca@hikvision.com

www.hikvision.ca

Disclaimer: This User Guide is for general information about Hikvision's NVR configuration system ("System") only. Hikvision's warranty of the System shall be subject to Hikvision RMA policy available at <https://ca.hikvision.com/en/support-resources/warranty-rma/rma-policy-ca> where credit warranty will be voided for products with modification or alteration.

©2021 Hikvision USA Inc. and Hikvision Canada Inc. All rights reserved. Hikvision is a registered trademark of Hikvision Digital Technology Co., Ltd. in the US, Canada and other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Product specifications and availability are subject to change without notice.