



HIKVISION

**Perimeter Protection
Recommended Product list**

HIKVISION[®]






Application: Gated Communities/Villa



Product Model	Picture	Description	Note
PCI-LB15F2SL(2.8mm) PCI-LB15F4SL(4mm) PCI-LB15F6SL (6 mm)		2688 × 1520 Resolution @ 30 fps Strobe Light and Audio Alarm False Alarm Reduction/Vehicle Detection IP66	
DS-2TD1217-2/PA(1.8mm) DS-2TD1217-3/PA(3.1mm) DS-2TD1217-6/PA(6.2 mm)		160x120 Thermal Resolution 4MP Optical Resolution Line Crossing, Intrusion, Region Entrance/ Exit with Human and Vehicle Filtering	
DS-7608NI-I2/8P		8 Channel Network Recorder	
DS-D5022FC		22-Inch' Monitor VGA/HDMI Input	
DS-3E0510P-E		8 Channel PoE Port Switch	

Application: Warehouses/Office Buildings



Product Model	Picture	Description	Note
DS-2TD2617-3/PA DS-2TD2617-6/PA DS-2TD2617-10/PA		Thermal resolution 160x120 Lens: 3.1/6.2/9.7mm VCA range: 21m/42m/70m (68ft/137ft/229ft) False Alarm Reduction Strobe Light and Voice Alarm	
DS-7608NI-I2/8P		8 Channel Network Recorder	
HikCentral Professional		Centralized Video Management and Alarm Handling	Optional
DS-D5022FC		22-Inch Monitor VGA/HDMI Input	
DS-3E0510P-E		8 Channel PoE Port Switch	





Application: Construction Site



Product Model	Picture	Description	Note
PCI-LB15F2SL(2.8mm) PCI-LB15F4SL(4mm) PCI-LB15F6SL (6 mm)		2688 × 1520 Resolution @ 30 fps 2592 × 1944 Resolution @ 20 fps Strobe light and audio alarm False Alarm Reduction/Vehicle Detection IP66	
DS-7716NI-I4/16P		8 Channel Network Recorder	
DS-3E0510P-E		8 Channel PoE Ports Switch	Optional

Application: Factory



Product Model	Picture	Description	Note
iDS-2SR8141IXS-AB		4 MP 40 × Radar PTZ Camera Lens: 6.0 mm to 240 mm Up to 2560 × 1440 @ 60 fps resolution 100m~1500m (328ft~4921ft) working distance IP67, Lightning & Surge Protection & Voltage Transient Protection	
iDS-7716NI-I4/16P		16 Channel Video Recorder	
DS-3E0510P-E		8 Channel PoE Port Switch	
DS-D5043FL-B		43-inch FHD LCD monitor, LED Backlit Technology VGA/HDMI/ BNC, CVBS, DVI inputs	

Application: Perimeter Protection For Large Open Outdoor Area



Product Model	Picture	Description	Note
DS-2TD2637-10/P DS-2TD2637-15/P DS-2TD2637-25/P DS-2TD2637-35/P		Thermal: 384x× 288 Lens: 15/25/35mm False Alarm Reduction VCA range: 150m/250m/350m	Bullet or PTZ or combination of both
DS-2DF9C245IHS-DLW		45x Outdoor IR PTZ, DarkfighterX Up to 1920 × 1080 Resolution VCA range: 670.3 m (2199.1ft)	
DS-7716NI-I4/16P		16 Channel Network Recorder	
DS-3E0510P-E		8 Channel PoE Port Switch	Optional
DS-D5032FL		32-Inch LCD Monitor VGA/HDMI/ BNC and USB Inputs	
HikCentral Professional		Centralized Video Management and Alarm Handling	