

DS-2CD2625FWD-IZS

2 MP Ultra-Low Light Network Bullet Camera

Powered by
DarkFighter™



H.265+

- 1/2.8" Progressive Scan CMOS
- Full 1080p @ 30 fps
- Ultra-Low Light, 0.0068 Lux, Darkfighter Technology
- H.265+, H.265, H.264+, H.264
- 120dB WDR
- BLC/3D DNR/ROI
- 12 VDC and PoE (802.3af)
- EXIR 2.0 with up to 165 ft (50 m) IR Range
- MicroSD Card Slot Supports 128 GB
- IP67, IK10 Protection

Hikvision's DS-2CD2625FWD-IZS provides important new technology for any security application. The H.265+ codec assures savings in bandwidth and storage. The DarkFighter Ultra-Low Light technology allows for use in the most demanding lighting conditions. EXIR 2.0 technology enhances night time performance.

Available models:
DS-2CD2625FWD-IZS




Specifications

DS-2CD2625FWD-IZS

Camera	
Image Sensor	1/2.8" progressive scan CMOS
Minimum Illumination	Color: 0.005 lux @ [f/1.2, AGC on], 0 lux with IR, color: 0.0068 lux @ [f/1.4, AGC on], 0 lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Supported
Day/Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	120 dB
3-Axis Adjustment	Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°
Lens	
Focal Length	2.8 to 12 mm (motorized)
Aperture	f/1.4
FOV	Horizontal field of view: 105° to 35°; vertical field of view: 56° to 20°; diagonal field of view: 126° to 40.5°
Lens Mount	Ø14
IR	
IR Range	Up to 165 ft (50 m)
Wavelength	850 nm
Compression Standard	
Video Compression	Main stream: H.265+/H.265/H.264+/H.264; sub stream: H.265/H.264/MJPEG; third stream: H.265/H.264
H.264 Type	Main profile/high profile
H.265 Type	Main profile
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio Bit Rate	64 Kbps [G.711]/16 Kbps [G.722.1]/16 Kbps [G.726]/32 to 192 Kbps [MP2L2]
Smart Features	
Behavior Analysis	Line crossing detection, intrusion detection, unattended baggage detection, object removal detection
Face Detection	Supported
Region of Interest	Supports one fixed region for main stream and sub stream
Image	
Maximum Resolution	1920 × 1080
Main Stream	30 fps [1920 × 1080, 1280 × 960, 1280 × 720]
Sub Stream	30 fps [640 × 360, 352 × 240]
Third Stream	30 fps [1920 × 1080, 1280 × 720, 640 × 360, 352 × 240]
Image Enhancement	BLC/3D DNR
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or Web browser
Day/Night Switch	Auto/schedule/triggered by alarm in
Network	
Network Storage	Supports microSD/SDHC/SDXC card (128 GB), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error, alarm input, alarm output
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General Function	One-key reset, anti-flicker, three streams, heartbeat, password protection, privacy mask, watermark, IP address filter
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users; 3 levels: administrator, operator and user
Client	iVMS-4200, Hik-Connect
Web Browser	IE 8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
Interface	
Audio	1 input (line in, 3.5 mm), 1 output (3.5 mm), mono sound
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Alarm	1 input, 1 output (maximum 12 VDC, 30 mA)
Video Output	1Vp-p composite output (75 Ω/BNC)
On-Board storage	Built-in microSD/SDHC/SDXC slot, up to 128 GB
SVC	Supports H.264 and H.265 encoding
Reset Button	Supported
Audio	
Environment Noise Filtering	Supported
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz
General	
Operating Conditions	-22° to 140° F [-30° to 60° C]
Power Supply	12 VDC ±25%, PoE (802.3af); terminal block for DC input
Power Consumption and Current	12 VDC, 1.2A, maximum 14.5 W, PoE (802.3at, 42.5 to 57 V), 0.5 to 0.1 A, maximum 16.5 W
Protection Level	IP67, IK10, TVS 2000V lightning protection, surge protection, and voltage transient protection
Material	Metal
Dimensions	Ø5.67" × 13.10" [Ø144.13 × 332.73 mm]
Weight	Camera: 4.17 lbs (1.89 kg)

Accessories



Dimensions

